

M_FR

	REF / ART.NR	DIMENSIONS								COMPRESSION		RIGIDITE
		ØA	B	C	D	E	F	G	M	CHARGE	FLECHE	
		mm.								kg.	mm.	kg./cm
M	M25	55	79						8	25	20±2,0	12,50
	M50	55	79						8	50	20±2,0	25,00
	M75	55	79						8	75	20±2,0	37,50
	M100	55	79						8	100	20±2,0	50,00
	M125	55	79						8	125	20±2,0	62,50
	M150	73	116						12	150	30±3,0	50,00
	M200	73	116						12	200	30±3,0	66,67
	M250	73	116						12	250	30±3,0	83,33
	M350	73	116						12	350	30±3,0	116,67
	M450	73	116						12	450	30±3,0	150,00
	M550	73	116						12	550	30±3,0	183,33
	M25B	55	81	90	55	70	10	10	8	25	20±2,0	12,50
	M50B	55	81	90	55	70	10	10	8	50	20±2,0	25,00
	M75B	55	81	90	55	70	10	10	8	75	20±2,0	37,50
	M100B	55	81	90	55	70	10	10	8	100	20±2,0	50,00
	M125B	55	81	90	55	70	10	10	8	125	20±2,0	62,50
	M150B	73	119	110	75	89	11	10	12	150	30±3,0	50,00
	M200B	73	119	110	75	89	11	10	12	200	30±3,0	66,67
	M250B	73	119	110	75	89	11	10	12	250	30±3,0	83,33
	M350B	73	119	110	75	89	11	10	12	350	30±3,0	116,67
	M450B	73	119	110	75	89	11	10	12	450	30±3,0	150,00
	M550B	73	119	110	75	89	11	10	12	550	30±3,0	183,33
	M25BB		83	90	55	70	10	10		25	20±2,0	12,50
	M50BB		83	90	55	70	10	10		50	20±2,0	25,00
	M75BB		83	90	55	70	10	10		75	20±2,0	37,50
	M100BB		83	90	55	70	10	10		100	20±2,0	50,00
	M125BB		83	90	55	70	10	10		125	20±2,0	62,50
	M150BB		120	110	75	89	11	10		150	30±3,0	50,00
	M200BB		120	110	75	89	11	10		200	30±3,0	66,67
	M250BB		120	110	75	89	11	10		250	30±3,0	83,33
M350BB		120	110	75	89	11	10		350	30±3,0	116,67	
M450BB		120	110	75	89	11	10		450	30±3,0	150,00	
M550BB		120	110	75	89	11	10		550	30±3,0	183,33	

