

NT2_FR

	REF / ART.NR	DIMENSIONS				COMPRESSION		RIGIDITE
		ØA	B	D	C	CHARGE	FLECHE	
		mm.				kg.	mm.	kg./cm
N T2	N10T2	55	59	M-08	25	10	11±2,0	9,09
	N15 T2	55	59	M-08	25	15	11±2,0	13,64
	N25T2	55	59	M-08	25	25	11±2,0	22,73
	N50T2	55	59	M-08	25	50	11±2,0	45,45
	N75T2	55	59	M-08	25	75	11±2,0	68,18
	N100T2	55	59	M-08	25	100	11±2,0	90,91
	N150T2	73	91	M-12	33	150	13±2,0	115,38
	N250T2	73	91	M-12	33	250	13±2,0	192,31
M T2	N350T2	73	91	M-12	33	350	13±2,0	269,23
	M25T2	55	79	M-08	25	25	20±2,0	12,50
	M50T2	55	79	M-08	25	50	20±2,0	25,00
	M75T2	55	79	M-08	25	75	20±2,0	37,50
	M100T2	55	79	M-08	25	100	20±2,0	50,00
	M125T2	55	79	M-08	25	125	20±2,0	62,50
	M150T2	73	120	M-12	33	150	30±3,0	50,00
	M200T2	73	120	M-12	33	200	30±3,0	66,67
	M250T2	73	120	M-12	33	250	30±3,0	83,33
	M350T2	73	120	M-12	33	350	30±3,0	116,67
	M450T2	73	120	M-12	33	450	30±3,0	150,00
	M550T2	73	120	M-12	33	550	30±3,0	183,33

